

Type HT xxxx SPC or SCA

镀银铜芯聚酰亚胺薄膜和PTFE生带复合绝缘轻型航空导线

-90 ~ +200°C

LIGHT WEIGHT

薄壁轻量型

VOLTAGE RATING 250V AC

交流250伏额定电压

SILVER PLATED COPPER CONDUCTOR

高导镀银铜丝导体

UV LASER PRINTABLE

表面可激光打印标记

ARC TRACKING RESISTANT

耐电弧

MOULD AND FUNGUS RESISTANT

防霉抗真菌

VERY GOOD RESISTANCE TO AIRCRAFT FLUIDS

优良的航空煤油耐受性

Insulation: polytetrafluoroethylene/ Polyimide composite tape

绝缘: 聚四氟乙烯/聚酰亚胺复合薄膜

Operating temperature: -90 ~ +200°C

工作温度: -90 ~ +200°C

Voltage rating: 250 Volts AC

额定电压: 交流250伏

Wall thickness: 0.115 mm


绝缘壁厚: 0.115 mm

Standard colors: Black, Brown, Red, Orange, Yellow, Green, Blue, Purple, Gray, White, other colors upon request(striped color available).

标准颜色: 黑、棕、红、橙、黄、绿、蓝、紫、灰、白, 可按要求定制 (可定制双色线)

Standard multicore: twisted pairs, twisted triples, twisted quads, etc.

多芯电缆: 双绞线、三芯绞合、四芯绞合, 等。有无护套, 有无屏蔽均可。



CONSTRUCTION/ 产品结构

- Conductor/ 导体
electrolytic silver plated annealed copper or high strength silver plated copper alloy (SCA)
退火镀银电解铜或高强度镀银铜合金
- Insulation/ 绝缘
Wrapped and sealed FP/Polyimide composited tape
聚四氟乙烯/聚酰亚胺复合薄膜带绕包并烧结
- Jacket/ 护套
PTFE tape top wrapped and sintered for coloring, UV laser printable
聚四氟乙烯薄膜绕包并烧结, 标识电线不同的颜色, 电线表面可激光打印标记

APPLICATION/ 应用

Our Polyimide & PTFE composited insulated wire is designed for the harshest environments and extreme conditions. This wire may be used in commercial or military aircraft where wire applications must adhere to certain restrictions and specifications. Our high-performance wire meets requirements for small dimensions, high-temperature resistance, low weight, and low flame propagation.

我们的聚酰亚胺/聚四氟乙烯复合绝缘航空导线专为恶劣环境和极端条件而设计。这类电线可用于那些对电线的的使用坚持严格要求和规范的商用或军用飞机。我们的高性能电线满足小尺寸、耐高温、轻量化和低火焰传播的要求。

PART NUMBER 产品编码	AWG 美规线号	CONDUCTOR/ 导体				INSULATED WIRE/ 成品电线		
		CONSTRUCTION 导体结构 (NB × Ø mm)	NOMINAL Ø 标称直径 (mm)	NOMINAL AREA 标称横截面 (mm ²)	NOMINAL RESISTANCE 标称直流电阻 (Ω / 100m)	NOMINAL Ø 标称完成外径 (mm)	APPROX. WEIGHT 成品约重 (g/m)	
HT 3001	30	1/ 0.254	0.254	0.051	35	0.48	0.60	
HT 3007	30	7/ 0.102	0.303	0.057	34	0.53	0.70	
HT 2801	28	1/ 0.320	0.320	0.081	21	0.55	0.90	
HT 2807	28	7/ 0.127	0.381	0.088	20	0.61	1.00	
HT 2601	26	1/ 0.403	0.403	0.13	13	0.63	1.40	
HT 2619	26	19/ 0.102	0.504	0.15	12	0.74	1.70	
HT 2401	24	1/ 0.510	0.510	0.21	8.5	0.74	2.10	
HT 2419	24	19/ 0.127	0.634	0.24	7.5	0.86	2.60	
HT 2201	22	1/ 0.644	0.644	0.33	5.3	0.87	3.20	
HT 2219	22	19/ 0.160	0.800	0.38	4.7	1.03	4.00	
HT 2001	20	1/ 0.812	0.812	0.52	3.3	1.04	5.00	
HT 2019	20	19/ 0.203	1.009	0.62	2.9	1.24	6.20	
HT 1819	18	19/ 0.254	1.269	0.96	1.9	1.50	9.60	
HT 1619	16	19/ 0.300	1.500	1.34	1.3	1.73	13.2	